

## Temperature recorder with printer, 2x binary input

code: G024I



Complete solution for temperature record during the transport.

- ♦ print-out of temperature record during transport of food, pharmaceuticals, flowers, live animals and other goods
- ♦ designed especially for installation in driver's cabin
- ♦ easy installation

### Technical data

TEMPERATURE SENSOR - external probe Pt1000	
Measuring range	-90 to +260 °C
Accuracy	±0.2 °C
Resolution	0.1 °C
GENERAL TECHNICAL DATA	
Operating temperature	-30 to +65 °C
Channels	2x external temperature probe, 2x binary input
Memory	1MB (approx. 170 000 hodnot)
Recording interval	adjustable from 60 seconds to 60 minutes
Display and alarm refresh	each 10 s
Recording mode	cyclic - after filling memory oldest data is overwritten by new
Real time clock	year, leap year, month, day, hour, minute, second
Power	9 to 32 V dc, protected against alternator load shedding + internal Lithium battery
Consumption while printing/not printing	approx. 8 W/approx. 0,1 W
Protection class	IP20
Dimensions	175 x 124 x 51 mm
Weight	approx. 700 g
Warranty	3 years

Distributor in Australia  
**Pacific Sensor Technologies Pty Ltd.**  
 Unit 4, 3 Neutron Place, Rowville, VIC3178 Australia  
 1300 662 720  
[sales@pacificsensortech.com.au](mailto:sales@pacificsensortech.com.au)  
[www.pacificsensortech.com.au](http://www.pacificsensortech.com.au)